


13900

Tuckahoe Trading Inc



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCTS AND COMPANY IDENTIFICATION

PRODUCT NAME: RESIN-OFF
SYNONYMS: COMPOUNDED PETROLEUM HYDROCARBONS
CAS NO: 64742-43-4
COMPANY NAME: TUCKAHOE TRADING COMPANY
 94 N HAMILTON STREET
 DOYLESTOWN, PA 18901
TELEPHONE AND REGULATORY INFORMATION: 2215-345-9275

2. COMPOSITION & INFORMATION ON INGREDIENTS

COMPONENT	CAS NO	%	TWA/CEILING	REFERENCE
WAX FUMES ONLY	64742-43-4	100%		

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
APPEARANCE AND ODOR: WHITE SOLID, MILD WAXY ODOR
STATEMENT OF HAZARD:
 CAUTION: MAY CAUSE EYE AND SKIN IRRITATION
POTENTIAL HEALTH EFFECTS:
EFFECTS OF OVEREXPOSURE:
Inhalation: Exposure to spray or mist cause irritation of respiratory passages.
Skin: Prolonged or repeated contact with skin may lead to drying or irritation.
Eyes: Eye contact may cause mild to moderate irritation

4. FIRST AID MEASURES

IN CASE OF SKIN CONTACT, WASH AFFECTED AREAS OF SKIN WITH SOAP AND WATER.
IN CASE OF EYE CONTACT, IMMEDIATELY IRRIGATE WITH PLENTY OF WATER FOR 15 MINUTES.
IF OVERCOME BY FUMES REMOVE TO FRESH AIR IMMEDIATELY AND CONSULT A PHYSICIAN.
IF BURNED BY MOLTEN PRODUCT, QUENCH IMMEDIATELY WITH COLD TAP WATER. DRY BURN AREA AND LOOSELY COVER TO PROTECT FROM INFECTION. CONSULT A PHYSICIAN

5. FIRE FIGHTING MEASURES:

FLASH POINT: 420 F
FLAMMABLE LIMITS
FLAMMABLE PROPERTIES
METHOD: ASTM D-92
 (% by vol): not available
 AUTOIGNITION TEMP: NOT AVAILABLE
 DECOMPOSITION TEMP: NOT AVAILABLE

EXINGUISHING MEDIA AN FIRE FIGHTING INSTRUCTIONS

Use water spray, carbon dioxide or dry chemical to extinguish fires. Use water to keep containers cool. Wear self contained positive pressure breathing apparatus.