

8954

		Page: 1
SAFETY DATA SHEET		Revision Date: 01/7/2018
		Print Date: 1/7/2018
		SDS Number: A-201
Pliobond™ 20 ADHESIVE ™ Trademark, Ashland or its subsidiaries, registered in various countries 162497	Packaged and Marketed by: The Ruscoe Company 485 Kenmore Blvd Akron, OH 44301 Phone:330-253-8148 Toll Free:800-293-8148 Fax: 330-253-2933	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**Product identifier**

Trade name : Pliobond™ 20
ADHESIVE
™ Trademark, Ashland or its subsidiaries, registered in
various countries

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet Ashland P.O. Box 2219 Columbus, OH 43216 United States of America (USA) 614-790-3333 EHSProductSafety@ashland.com	Emergency telephone number 1-800-ASHLAND (1-800-274-5263) Regulatory Information Number 1-800-325-3751 Product Information 614-790-3333
---	---

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A


Skin sensitization : Category 1

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 1B

Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

Specific target organ systemic toxicity - repeated exposure : Category 2 (Skin, Nervous system, Liver, Kidney)

	Page: 2
SAFETY DATA SHEET	Revision Date: 01/7/2018
	Print Date: 1/7/2018
	SDS Number: A-201
Pliobond™ 20 ADHESIVE ™ Trademark, Ashland or its subsidiaries, registered in various countries 162497	Packaged and Marketed by: The Ruscoe Company 485 Kenmore Blvd Akron, OH 44301 Phone:330-253-8148 Toll Free:800-293-8148 Fax: 330-253-2933

GHS label elements

Hazard pictograms



Signal Word


: Danger

Hazard Statements

: Highly flammable liquid and vapor.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Suspected of causing genetic defects.
May cause cancer.
May cause damage to organs (Skin, Nervous system, Liver, Kidney) through prolonged or repeated exposure.

Precautionary Statements

: **Prevention:**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation or rash occurs: Get medical advice/ attention.

Page: 3	
 Ashland always solving	
SAFETY DATA SHEET	Revision Date: 01/7/2018
	Print Date: 1/7/2018
	SDS Number: R0171288
Pliobond™ 20 ADHESIVE ™ Trademark, Ashland or its subsidiaries, registered in various countries 162497	Packaged and Marketed by: The Ruscoe Company 485 Kenmore Blvd Akron, OH 44301 Phone:330-253-8148 Toll Free:800-293-8148 Fax: 330-253-2933

If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant
foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal
plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
METHYL ETHYL KETONE	78-93-3	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	76.792
CALCIUM CARBONATE	471-34-1	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	2.7452
PHENOL	108-95-2	Acute Tox. 3; H301 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1; H314	1.088